

**EVEREST****EVEREST IST-2002-001858****D16*****Final report on QoS management in the Core Network and QoS Mapping*****Contractual Date of Delivery to the CEC: 30-05-2005****Actual Date of Delivery to the CEC: 15-01-2006****Editor: Nima Nafisi (KCL)****Author(s): see list****Participant(s): UPC, KCL, PTIN, TI, TID, TEL****Workpackage: WP3****Est. person months: 8****Security: PU****Nature: Report****Version: 002****Total number of pages: 84****Abstract:**

In continuation of deliverable D08, this document further analyses the topics introduced previously: the Everest end-to-end QoS architecture encompassing CRRM and the bandwidth broker, a centralized IP QoS entity; QoS class mapping between RANs and the DiffServ domain; and finally the cross-issues between the bandwidth broker, QoS routing and the micromobility overlay. As novel contributions, the signalling message chart between the introduced QoS entities is given. The performance evaluation of previously introduced concepts like QoS class mapping and hierarchical bandwidth brokers has been done.

This document is an updated version of the one submitted by June 2005.

**Keyword list:** end-to-end QoS architecture, policy-based networking, DiffServ core network, mapping between DiffServ classes and radio QoS classes, hierarchy of bandwidth brokers, Wireless QoS Broker.

## **DISCLAIMER**

The work associated with this report has been carried out in accordance with the highest technical standards and the EVEREST partners have endeavoured to achieve the degree of accuracy and reliability appropriate to the work in question. However since the partners have no control over the use to which the information contained within the report is to be put by any other party, any other such party shall be deemed to satisfied itself as to the suitability and reliability of the information in relation to any particular use, purpose or application.

Under no circumstances will any of the partners, their servants, employees or agents accept any liability whatsoever arising out of any error or inaccuracy contained in this report (or any further consolidation, summary, publication or dissemination of the information contained within this report) and/or the connected work and disclaim all liability for any loss, damage, expenses, claims or infringement of third party rights.

**DOCUMENT HISTORY**

Date	Version	Status	Comments
2-05-2005	1.0	Int	ToC proposal
9-05-2005	2.0	Int	Initial Contributions of the partners
20-05-2005	3.0	Int	1 <sup>st</sup> Draft of D16 for comments
06-06-2005	4.0	Int	Contributions from the Partners
20-06-2005	5.0	Int	2 <sup>nd</sup> Draft for Comments
28-06-2005	6.0	Int	New version of D16 for Comments
1-07-2005	6.1	Int	Updated version with new results from simulation
8-07-2005	7.0	Int	Updated version of D16 including very specific comments
13-07-05	008	Int	Final version. To be approved by PCC
15-07-05	001	Apr	Approved version 1.0
15-12-05	009	Int	1 <sup>st</sup> Draft of updated version for comments
5-1-06	010	Int	2 <sup>nd</sup> Draft of the updated verion for comments
12-01-06	011	Int	Final version of the updated document
15-01-06	001	Apr	Approved version 2.0

Authors List

Fernando CASADEVALL (UPC)  
Ramon FERRUS (UPC)  
Antoni GELONCH (UPC)  
Nima NAFISI (KCL)  
Jordi PÉREZ-ROMERO (UPC)  
Costas SAMDANIS (KCL)  
Oriol SALLEN (UPC)  
Lin WANG (KCL)

## Executive summary

This document addresses the end-to-end QoS framework envisaged in the EVEREST project, in the context of beyond 3G systems. The document completes the end-to-end QoS architecture introduced in deliverable D08 and presents performance evaluation results. The document is basically divided in two main sections.

The first main section is devoted to explain the rationality of the end-to-end QoS architecture considered in the EVEREST project. This section completes the end-to-end QoS architecture introduced in deliverable D08, where the basis of such architecture was presented as an extension of 3GPP QoS framework for heterogeneous radio access networks. As major contributions, the architecture presented encompasses CRRM functionality support in the radio part and proposes a QoS control plane to jointly manage IP resources in the core network and radio bearers in the RANs. In this sense, functional entities and their roles in the overall QoS management framework have been identified and addressed in D08. In this section, the proposed architecture is further developed in terms of procedures and signalling and QoS class mapping between UMTS and DiffServ classes.

The second main section looks at the implications of the use of a BB, introduced by the Everest end-to-end QoS architecture, in an IP mobile access network. It is shown that the use of BB in an IP mobile access network implies the analysis of the interactions between BB, QoS routing and IP micromobility overlay. Thus, the mechanism involved in the initial access router selection and IP handover are presented for the different cases of a host-based or tunnel-based micromobility protocol and a source or hop-by-hop QoS routing protocol. Furthermore through simulation and analytical evaluation, it is shown that there is trade-off between scalability and QoS performance of the different cases. It is concluded that a hierarchy of BBs with hierarchical QoS routing areas presents a lower signalling overhead compared to a single BB with a single QoS routing area. Nonetheless a higher network utilisation can be achieved for a single BB with a single QoS routing area. And finally It is shown that for different network topologies, a tunnel-based micromobility protocol presents a higher disruption time during IP handover compared to a host-based micromobility protocol.

## Table of Contents

<b>1</b>	<b>INTRODUCTION .....</b>	<b>1</b>
<b>2</b>	<b>END-TO-END QOS ARCHITECTURE .....</b>	<b>1</b>
2.1.1	<i>Related work .....</i>	2
2.2	END TO END QOS ARCHITECTURE FOR HETEROGENEOUS WIRELESS NETWORKS .....	2
2.2.1	<i>3GPP QoS Architecture .....</i>	2
2.2.2	<i>QoS versus Over-provisioning in the Core Network .....</i>	4
2.2.3	<i>Proposed E2E QoS Architecture .....</i>	9
2.2.4	<i>Coupling Approach in the E2E Architecture .....</i>	13
2.3	MESSAGE SEQUENCE CHART FOR THE END-TO-END QoS SIGNALLING .....	20
2.3.1	<i>Signalling protocols .....</i>	21
2.3.2	<i>Reference Scenario .....</i>	22
2.3.3	<i>WQB and CRRM aspects .....</i>	25
2.3.4	<i>Connection Establishment .....</i>	26
2.3.5	<i>Vertical Handover .....</i>	28
2.4	MAPPING BETWEEN RANS QoS CLASSES AND DIFFSERV PHBs .....	29
2.4.1	<i>Considerations about mapping and network transport architecture .....</i>	30
2.4.2	<i>Relevant Scenarios in EVEREST .....</i>	32
2.4.3	<i>Simulator for QoS class mapping .....</i>	35
2.4.4	<i>Simulation results .....</i>	36
2.4.5	<i>Simulation results considering different CRRM algorithms .....</i>	44
2.4.6	<i>Further possible study for the QoS class mapping .....</i>	51
<b>3</b>	<b>SCALABLE QOS ARCHITECTURE FOR THE MOBILE ACCESS NETWORK BASED ON BANDWIDTH BROKERS .....</b>	<b>52</b>
3.1	BB AND QOS ROUTING .....	52
3.2	MICROMOBILITY AND QOS ROUTING .....	54
3.2.1	<i>Micromobility protocols .....</i>	54
3.2.2	<i>A new paradigm for mobility management encompassing QoS routing .....</i>	54
3.3	IP ACCES NETWORK SIMULATOR IMPLEMENTATION .....	56
3.4	PERFORMANCE EVALUATION .....	59
3.4.1	<i>QoS performance .....</i>	59
3.4.2	<i>Simulations with different background traffic scenarios .....</i>	63
3.4.3	<i>Scalability .....</i>	74
3.4.4	<i>Conclusions .....</i>	75
3.5	IP HANDOVER DELAY .....	75
3.5.1	<i>Analytical approach .....</i>	75
3.5.2	<i>Simulation approach .....</i>	79
<b>4</b>	<b>CONCLUSIONS .....</b>	<b>80</b>
	<b>REFERENCES .....</b>	<b>81</b>
	<b>ACRONYMS .....</b>	<b>83</b>